

# SUPER HELP SRL

VIA VITTORIO VENETO, 11

21100 VARESE - ITALY

TEL +39-347-4650120

E-MAIL: [info@super-help.com](mailto:info@super-help.com)

WEB: [www.super-help.com](http://www.super-help.com)



## TECHNICAL DATA SHEET ZINK SPRAY

Ref. : 25400

UFI n. UK5E-N0CS-P00H-PJ5G

### 1. GENERAL DESCRIPTION

Combination of pure zinc and aluminum for durable protection of all metal surfaces. It safely adheres to all metals, guaranting an excellent protection against atmospheric agents. Highly resistant to salt and water. Quick drying. Water resistant after 30 minutes. Once dry, the application can be repeated for furtherly increasing the protective thickness.

### 2. FEATURES

- Ready to use, quick action, immediate results.
- Supplied quantity: 1,55 ± 0,05 gr in 10"
- Average yield: 4–5 m<sup>2</sup>×kg
- Drying time (in air at 20 °C):
  - Dust resistant: 30–45'
  - Dry to touch: 2–3 hours
  - Fully dry: 6–8 hours
- Salt spray test:
  - method ASTM B 117-09
  - temperature (C°): 35 +1,1 /- 1,7
  - 2 crossed product applications on laboratory metal sheets (Q-panel)
  - saline solution (% NaCl): 5
  - total test time: 500 hours
  - Results: Degree of rusting ( ASTM D 610-08): 4G (6%)
  - Coating Thickness ( ISO 2808-2007 MET 7C,d ): 58,4 µm

### 3. APPLICATIONS

Anti-rust, technical spray product for metals protection.

### 4. DIRECTIONS

- Surface to be treated must be degreased and clean.
- Shake well before use for 30 secs.
- Spray from 25-30 cm distance.
- Wait 8 to 10 minutes for a second application.
- After use, turn the can upside-down and spray to clean the nozzle.

### 6. PACKAGING

Aerosol : 12 x 400 ml

Bar code Nr. 8028687254006



Date : 2023-10-17