SUPER HELP SRL

VIA VITTORIO VENETO, 11 21100 VARESE - ITALY TEL +39-347-4650120

E-MAIL: info@super-help.com

WEB: www.super-help.com



TECHNICAL DATA SHEET TYRE REPAIR

Ref.: 1300 - 1400 - 1500

1. GENERAL DESCRIPTION

Tyre repair: Super Help tyre repair.

A rubber latex based aerosol product that re-inflates punctured tyres and at the same time seals the puncture. Super Help tyre repair is designed to give fast, temporary relief in emergency situations when changing a wheel with a flat tyre is inconvenient or even dangerous.

2. FEATURES

- Seals and inflates in a few seconds; enabling to drive to a service facility for examination and/or replacement by a professional.
- · Forms a stable, durable film inside the tyre.
- · This inner protective film lasts far beyond the life of the tyre itself.
- · Clean and easy to use on all types of tyres, tubed or tubeless, on all automotive vehicles.
- · Aerosols use propane/butane propellant to inflate the tyre from flat (no pressure) to driving pressure.

3. APPLICATIONS

Tyre types:

- tubed
- · tubeless
- radial
- · cross ply

As used for:

- · cars
- · trucks
- busses
- motorcycles
- · bicycle

4. DIRECTIONS

- · If possible, remove the cause of the puncture.
- · Shake well before use. In cold weather, warm the can with hands or in front of the car heating system.
- · Screw nozzle firmly onto tyre valve.
- · Remove protective seal from aerosol. Hold can upright. Press button to fill tyre. Continue until tyre is inflated. Disconnect.
- · Immediately drive 5 to 10 km, at moderate speed to allow the product to act.
- As soon as possible deflate tyre totally and refill tyre with compressed air to the prescribed pressure. Have your tyre examined by a professional and inform him about the use of this flammable product.
- · Always pump some air into the tyre to prevent the valve from becoming plugged.

6. PACKAGING

aerosol: 24 x 300 ml - 12 x 500 ml

REF 1300 - 300 ml Bar code Nr.8028687013009 ---- REF 1500 - 500 ml Bar code Nr.8028687015003



8 028687 015003

Date: 31-08-2010