SUPER HELP SRL

VIA VITTORIO VENETO, 11 21100 VARESE - ITALY TEL +39-347-4650120

E-MAIL: info@super-help.com

WEB: www.super-help.com



TECHNICAL DATA SHEET CHAIN GREASE

Ref.: 50150

1. GENERAL DESCRIPTION

Water resistant, adhesive chain lubricant. It is smooth and buttery in consistency for optimum surface coverage. Adhesive Lubricant penetrates deeply into vital chain pin and bushing areas, then sets to form an adhering, long lasting lubricant film. Designed even for highly loaded fast running chains used in corrosive, high power and shock load conditions.

2. FEATURES

- · Produces a high viscosity film.
- · Resists hot and cold water wash-off.
- · Resists high rpm sling-off.
- · Reduces friction and wear.
- · Reduces noise and vibration.
- · Extends chain life.
- · O-ring compatible.
- Harmless to metals and most plastics and rubbers (test before using on stressed plastic parts).
- · Aerosols use butan-propane propellant to maintain high pressure to the very last fluid in the can.

3. APPLICATIONS

Long lasting lubrication and protection of:

- · Chain drives.
- · Sprockets.
- · Open gears.
- Wire ropes.
- Pulleys.
- Snatch blocks.
- · Hoists.
- Conveyors.
- Forklifts.
- · Overhead door drives.
- · Motorcycle chains.
- Tractors and farm equipment.
- Construction site equipment.
- · Car wash equipment.
- Marine lubrication.

4. DIRECTIONS

- Shake can thoroughly before use.
- Use extension tube for precise aiming and hard-to-reach areas.
- Do not mix with other lubricants.
- · Apply evenly onto the chain, wire rope, etc. and allow product to penetrate and set for a few minutes.
- Do not energise or start high speed/high load equipment before product has penetrated.
- Use with adequate ventilation.
- · Do not apply while equipment is energised.

6. PACKAGING

aerosol: 12 x 150 ml

Bar code Nr. 8028687501506



Date: 31-08-2010