

SUPER HELP SRL

VIA VITTORIO VENETO, 11
21100 VARESE - ITALY
TEL +39-347-4650120
E-MAIL: info@super-help.com
WEB: www.super-help.com



TECHNICAL DATA SHEET PTFE LUB

Ref. : 40150

1. GENERAL DESCRIPTION

Superior lubricant with PTFE.

Super Help ptfе lub is a high performance lubricant incorporating a sophisticated additive package with PTFE to provide long lasting protection against friction, wear and corrosion. It out-performs conventional lubricants in lubricating effectiveness, increasing the life and operating efficiency of parts and equipment, especially under the extremes of pressures and the environment.

2. FEATURES

- PTFE addition helps to minimise surface to surface contact with an anti-friction shield.
- Withstands extreme load carrying situations.
- Outperforms conventional lubricants under extreme pressures.
- Penetrates and displaces moisture leaving a protective film.
- Safe on all metals and alloys.
- Testing is advised in case of doubt on painted surfaces, plastics and rubbers.
- Aerosols are equipped with an extension tube for added convenience.
- Aerosols use butan-propane propellant to maintain high pressure to the very last fluid in the can.

3. APPLICATIONS

A modern, versatile helper for hundreds of repair jobs in all working environments.

- Electrical parts : plugs, switches, coils, leads, ...
- Cars : ignition system, distributors, battery terminals, cables, starter motors, aerials, nuts and bolts, chrome, seat slides, door latches, spark plugs, ...
- Home : door locks and hinges, sliding doors and windows, drills, locks, hinges, catches, DIY tools, scissors, zippers, buggies, toys, ...
- Leisure : fishing gear, bicycles, garden tools, roller blades, roller skates, ski fittings, marine, golf buggies, ...
- Hundreds of other uses in : workshops, garages , building sites, factories, offices, gardens, homes, do-it-yourself, ...

4. DIRECTIONS

- Apply generously and allow penetrating. Full penetration may take a few minutes or more.
- For hard to reach areas, use extension tube.
- Use with adequate ventilation. Do not use on energized equipment.

6. PACKAGING

aerosol : 6 x 150 ml

Bar code Nr. 8028687401509



8 028687 401509

Date : 31-08-2010