

SUPER HELP SRL

VIA VITTORIO VENETO, 11
21100 VARESE - ITALY
TEL +39-347-4650120
E-MAIL: info@super-help.com
WEB: www.super-help.com



TECHNICAL DATA SHEET FLEXI COATING – BODY SPRAY

Ref. : 22500

1. GENERAL DESCRIPTION

Flexible, anti gravel and sound deadening compound developed to ensure long term stone chipping protection of vulnerable parts of vehicles. Corrosion preventive compound. Recommended for the protection of ferrous metals and the undersides of cars, trucks and trailers against corrosion and abrasive damage. Quick drying, can be painted over and is easy to apply. Directions for use: Shake well before use. Spray at room temperature. Clean the surface from grease and dirt before treatment. Allow the first coat to dry before applying further coats. After use, hold the can upside down and spray for a few seconds until no further product comes out from the nozzle.

2. FEATURES

- Creates a strong and elastic layer to prevent stone chipping.
- Corrosion preventive.
- Quick drying.
- Over coatable.

3. APPLICATIONS

- Before the product application, for minimum 24 hours, the product must be stored at room temperature between 10-35 °C.
- During application the product must be also used at room temperature between 10-35 °C.
- In case of painting over, the film must be totally dry.
- When using 2-component paints, first spray a thin layer of primer and after a sufficient drying time, the 2-component paint.

Surface preparation:

- The best performance of **FLEXI COATING** can be achieved only when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale.

Recommended Dry Film Thickness: 150/250 µm (microns)

Dry to touch time @ 20°C (minutes): 45

Cure time @ 20°C (hours): 24

Removal:

- **FLEXI COATING** is difficult to be removed, but in case use mineral spirits or any similar petroleum solvent, vapor degreasing, hot alkaline wash or low pressure steam.

4. USE

- Clean the surface from grease and dirt before treatment.
- Shake well before use.
- Spray at room temperature.
- Allow the first coat to dry before applying further coats.
- After use, hold the can upside down and spray for a few seconds until no further product comes out from the nozzle.

Note:

- The addition of any product over or under this coating is not recommended. The use of additional coatings could result in chemical incompatibility, thus affecting the performance of this coating.

5. LABEL ELEMENTS

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P211	Do not spray on an open flame or other ignition source.
P273	Avoid release to the environment.
P391	Collect spillage.

Contains:	XYLENE (MIXTURE OF ISOMERS) HYDROCARBONS, C6, ISOALCANI, <5% N-ESANO HYDROCARBONS, C7 n-alcani, isoalcani ACETONE
------------------	--

6. PACKAGING

Aerosol : 12 X 500 ml

Bar code Nr. 8028687225006



Date : 30-06-2020